


N71-14031
TMX-2145

NASA TECHNICAL
MEMORANDUM



NASA TM X-2145

NASA TM X-2145

CASE FILE
COPY



PREDICTION OF FRICTION AND
HEAT-TRANSFER COEFFICIENTS WITH
LARGE VARIATIONS IN FLUID PROPERTIES

by Maynard F. Taylor

Lewis Research Center

Cleveland, Ohio 44135

1. Report No. NASA TM X-2145	2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and Subtitle PREDICTION OF FRICTION AND HEAT-TRANSFER COEFFICIENTS WITH LARGE VARIATIONS IN FLUID PROPERTIES		5. Report Date December 1970	
		6. Performing Organization Code	
7. Author(s) Maynard F. Taylor		8. Performing Organization Report No. E-5221	
9. Performing Organization Name and Address Lewis Research Center National Aeronautics and Space Administration Cleveland, Ohio 44135		10. Work Unit No. 122-29	
		11. Contract or Grant No.	
12. Sponsoring Agency Name and Address National Aeronautics and Space Administration Washington, D. C. 20546		13. Type of Report and Period Covered Technical Memorandum	
		14. Sponsoring Agency Code	
15. Supplementary Notes			
16. Abstract <p>The conventional methods of predicting single-phase turbulent heat-transfer and friction coefficients often give values that are in poor agreement with measured values when large variations in the fluid properties are present. Heat-transfer and friction data for hydrogen, helium, nitrogen, air, and carbon dioxide were used to determine the best available relation for correlating friction and heat-transfer coefficients for heat addition to, and heat extraction from, gases flowing subsonically through a smooth tube.</p>			
17. Key Words (Suggested by Author(s)) Heat transfer coefficients; Friction coefficients; Variable properties; Smooth tube; Subsonic; Turbulent flow		18. Distribution Statement Unclassified - unlimited	
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No. of Pages 13	22. Price* \$3.00

PREDICTION OF FRICTION AND HEAT-TRANSFER COEFFICIENTS WITH LARGE VARIATIONS IN FLUID PROPERTIES

by Maynard F. Taylor
Lewis Research Center

SUMMARY

The conventional methods of predicting single-phase turbulent heat-transfer and friction coefficients often give values that are in poor agreement with measured values when large variations in the fluid properties are present. Heat-transfer and friction coefficients calculated by recently reported prediction equations were compared with measured values for hydrogen, helium, nitrogen, air, and carbon dioxide from several different investigations.

For the case of heat extraction from a gas the heat-transfer coefficient can be accurately predicted with the relation

$$Nu_b = 0.023 Re_b^{0.8} Pr_b^{0.4}$$

and for the case of heat addition with the relation

$$Nu_b = 0.023 Re_b^{0.8} Pr_b^{0.4} \left(\frac{T_s}{T_b} \right)^{-C_2}$$

where Nu_b is the bulk Nusselt number, Re_b is the bulk Reynolds number, Pr_b is the bulk Prandtl number, T_s is the surface temperature, and T_b is the bulk temperature.

For both heat extraction and heat addition to a gas the friction coefficient can be accurately predicted by the relation

$$\frac{f}{2} = \left(0.0007 + \frac{0.0625}{Re_s^{0.32}} \right) \left(\frac{T_s}{T_b} \right)^{-C_2}$$

where f is the friction coefficient, Re_s is the modified surface Reynolds number, T_s is the surface temperature, and T_b is the bulk temperature.

For both friction and heat transfer the exponent of the temperature ratio T_s/T_b is

$$C_2 = 0.57 - \frac{1.59}{x/D}$$

where x is the distance from the entrance of the test section and D is the inside diameter of the test section. These prediction equations are applicable to gases flowing subsonically through a smooth tube.

INTRODUCTION

Large variations in the physical properties of gases flowing turbulently through tubes have been found to greatly affect the heat-transfer and friction coefficients. The conventional "reference temperature" methods (i. e., evaluating the properties and density at a reference temperature $T_X = X(T_s - T_b) + T_b$) can predict coefficients that are greatly in error. For example, figure 1 shows that the measured friction coefficient




Figure 1. - Variation of local and average friction coefficients with modified film Reynolds number. Viscosity and density evaluated at film temperature.

can be as much as three times the value predicted by the Kármán-Nikuradse equation with the physical properties evaluated at the film temperature $T_f = (T_s + T_b)/2$:

$$\frac{1}{\sqrt{8 \frac{f_f}{2}}} = 2 \log Re_f \sqrt{8 \frac{f_f}{2}} - 0.8 \quad (1)$$

Errors of the same magnitude are found when measured heat-transfer coefficients are compared with those calculated by

$$Nu_f = 0.021 Re_f^{0.8} Pr_f^{0.4} \quad (2)$$

Equations (1) and (2) are applicable only for developed flow.

The use of the ratio of surface to fluid-bulk temperatures T_s/T_b raised to a power has been very successful in correlating both friction coefficients (ref. 1) and heat-transfer coefficients (ref. 2) with large variations in the fluid properties. The study of available friction data (ref. 1) resulted in the recommendation that the modified surface Reynolds number $Re_s = VD/\nu_s$ be used in correlating the friction coefficients. It appeared that a modified surface Reynolds number of 3000 was critical, and the following correlation equations were recommended:

For $Re_s < 3000$:

$$\frac{f}{2} = \frac{8}{Re_s} \quad (3)$$

For $Re_s \geq 3000$:

$$\frac{f}{2} = \left(0.0007 + \frac{0.0625}{Re_s^{0.32}} \right) \left(\frac{T_s}{T_b} \right)^{-0.5} \quad (4)$$

The recommended correlation equation for heat addition ($T_s/T_b > 1.0$) to hydrogen, helium, and nitrogen (ref. 2) is

$$Nu_b = 0.023 Re_b^{0.8} Pr_b^{0.4} \left(\frac{T_s}{T_b} \right)^{-C_2} \quad (5)$$

where

$$C_2 = 0.57 - \frac{1.59}{\frac{x}{D}}$$

Because of the great interest in hydrogen as a propellant for both nuclear and advanced chemical rockets, a large amount of heat-transfer data has been reported. These data cover a wide range of conditions, including surface to fluid-bulk temperature ratios to 23 and heat flux to 46 megawatts per square meter (28 Btu/sec-in.²).

Even though equations (3) to (5) predict friction and heat-transfer coefficients with much greater accuracy than has been possible heretofore, some interesting questions have been prompted by combining the friction and heat-transfer studies. One concerns the possibility of inserting the most recent exponent of T_s/T_b from the heat-transfer correlation equation (5) into the prior friction correlation equation (4) to make it applicable to smaller values of x/D . Another point of importance is that the friction equation (4) appears to apply to both heat addition ($T_s/T_b > 1.0$) and heat extraction ($T_s/T_b < 1.0$), but the heat-transfer equation (5) has been tested only for $T_s/T_b > 1.0$. The question of the applicability of equation (5) to heat extraction ($T_s/T_b < 1.0$) is certainly of interest. This investigation explored and answered these two questions.

SYMBOLS

C_1	constant used in eq. (6)
C_2	exponent of T_s/T_b
c_p	specific heat at constant pressure
D	inside diameter of test section
$f/2$	half bulk friction coefficient
$f_f/2$	half film friction coefficient
G	mass flow rate per unit cross-sectional area
h	local heat-transfer coefficient
k	thermal conductivity of gas
L	length of test section
Nu	Nusselt number, hD/k
Re	Reynolds number, VD/ν
Pr	Prandtl number, $c_p\mu/k$
T	temperature
V	velocity
X	parameter used in reference temperature equation
x	distance from entrance of test section
μ	absolute viscosity of gas
ν	kinematic viscosity of gas, μ/ρ
ρ	density of gas

Subscripts:

- b fluid bulk (denotes evaluation at fluid bulk temperature, T_b)
- cal calculated
- ex experimental
- f film (denotes evaluation at film temperature, $T_f = (T_s + T_b)/2$)
- s surface (denotes evaluation at surface temperature, T_s)

CORRELATION EQUATIONS

Heat-Transfer Coefficients

Several investigators have used the same basic equation

$$Nu_b = C_1 Re_b^{0.8} Pr_b^{0.4} \left(\frac{T_s}{T_b} \right)^{-C_2} \quad (6)$$

(with C_1 varying from 0.021 to 0.024 and C_2 varying with x/D as shown in fig. 2) to




Figure 2. - Variation of exponent of ratio of surface to fluid-bulk temperatures with axial distance from entrance of test section.

correlate heat-transfer coefficients for helium and air (ref. 3), hydrogen and helium (ref. 4), and nitrogen (ref. 5) for T_s/T_b to 8.0. The availability of hydrogen heat-transfer data taken over a wide range of conditions led to a thorough study of both the data and the many proposed correlation equations (ref. 2). The study recommended the use of the correlation equation

$$Nu_b = 0.023 Re_b^{0.8} Pr_b^{0.4} \left(\frac{T_s}{T_b} \right)^{-C_2} \quad (5)$$

where

$$C_2 = 0.57 - \frac{1.59}{\frac{x}{D}}$$

for all single-phase flow outside the near-critical region and for $2 < x/D < 252$. Equation (5) was used to calculate more than 3600 heat-transfer coefficients for hydrogen, and 87 percent deviated less than ± 25 percent from the measured coefficients. In addition to the hydrogen data, 88 nitrogen gas and 359 helium gas heat-transfer coefficients were predicted with equation (5), and 98 percent deviated less than ± 25 percent from the measured coefficients. All the data used in reference 2 involved heat addition to the gas ($T_s/T_b > 1$), and equation (5) was not tested on data with heat extracted from the gas ($T_s/T_b < 1$).

In the present investigation, heat-transfer coefficients for heat extraction from air and carbon dioxide (ref. 6) and air (ref. 7) were used to test equation (5) for its applicability in the range $0.25 < T_s/T_b < 1.0$. Predicted heat-transfer coefficients using equation (5) are as much as twice the measured coefficients. These results suggest that the term $\left(T_s/T_b \right)^{-C_2}$ does not apply to $T_s/T_b < 1.0$. To determine the effect of $T_s/T_b < 1.0$ on the heat-transfer coefficients, the term $\left(T_s/T_b \right)^{-C_2}$ was omitted from equation (5) to give

$$Nu_b = 0.023 Re_b^{0.8} Pr_b^{0.4} \quad (7)$$

Heat-transfer coefficients predicted using equation (7) are in good agreement with the measured data, 81 percent of the calculated coefficients deviating less than ± 15 percent from the measured values. No effect of T_s/T_b appears to be present.

Reference 6 also reported heat-transfer coefficients for heat addition to air and carbon dioxide. Where equation (5) was used to predict these heat-transfer coefficients, 93 percent of the calculated coefficients deviated less than ± 25 percent from the measured values.

Friction Coefficients

The study of friction coefficients (ref. 1) which recommended the following equation for modified surface Reynolds numbers of 3000 or greater

$$\frac{f}{2} = \left(0.0007 + \frac{0.0625}{\text{Re}_s^{0.32}} \right) \left(\frac{T_s}{T_b} \right)^{-0.5} \quad (4)$$

used both local and average friction data for both heat addition and extraction (refs. 4, 6, and 8 to 12). Equation (4) correlated local friction coefficients for x/D from 16 to 113. Because equation (5) correlates heat-transfer coefficients for an x/D as low as 2, an obvious step is to use the exponent of T_s/T_b from the heat-transfer equation (5) in the friction equation (4), which gives

$$\frac{f}{2} = \left(0.0007 + \frac{0.0625}{\text{Re}_s^{0.32}} \right) \left(\frac{T_s}{T_b} \right)^{-C_2} \quad (8)$$

where

$$C_2 = 0.57 - \frac{1.59}{\frac{x}{D}}$$

Local friction coefficients for heat extraction from air and carbon dioxide (ref. 6) were compared with coefficients predicted using equation (8), and the agreement was very good for $5 < x/D < 57$ (the limit of the experimental data with the exception of the first data point which was at an $x/D = 1.57$). Equation (8) predicts local friction coefficients which are in good agreement with measured values for both heat extraction ($0.3 < T_s/T_b < 1.0$) and heat addition ($1.0 < T_s/T_b < 7.35$) for x/D from 5 to 113.

DISCUSSION OF RESULTS

Heat-Transfer Coefficients

The relation shown in equation (7) was used to calculate heat-transfer coefficients for heat extraction from air and carbon dioxide (ref. 6) and air (ref. 7). The coefficients for air and carbon dioxide (ref. 6) were calculated using equation (7), with 80 percent of them deviating less than ± 15 percent from the measured coefficients for x/D from 5 to 52. Air data (ref. 7) measured only in the entrance section of a tube at x/D of 1.5, 4, 7, and 10 were also calculated using equation (7), with 86 percent of the calculated values deviating less than ± 15 percent from the measured values for x/D of 4, 7, and 10. The calculated coefficients at x/D of 1.5 ran 15 to 30 percent lower than measured values.

The additional data for heat added to air and carbon dioxide (ref. 6) were local heat-transfer coefficients for x/D from 0.22 to 59 and T_s/T_b to 2.8. Using equation (5), 98 percent of the calculated heat-transfer coefficients for air deviated less than ± 15 percent for x/D from about 2 to 59. The calculated values for carbon dioxide for the same x/D did not agree as well as the air data, with 88 percent deviating less than ± 25 percent. Table I summarizes the results of both the present investigation and reference 2.

TABLE I. - PERCENT OF PREDICTED LOCAL HEAT-TRANSFER
COEFFICIENTS THAT DEVIATE LESS THAN ± 25 PERCENT
FROM EXPERIMENTAL COEFFICIENTS
FOR VARIOUS GASES

Gas	Number of data points	Percent of h_{cal} that deviate less than ± 25 percent from h_{ex}
Heat added to gas, $1.0 < T_s/T_b < 23$; calculations used eq. (5)		
Hydrogen	3674	87
Helium	359	98
Nitrogen	88	97
Air	370	97
Carbon dioxide	370	88
Heat extracted from gas, $0.25 < T_s/T_b < 1.0$; calculations used eq. (7)		
Air	641	86
Carbon dioxide	550	94

Friction Coefficients

The relation shown in equation (8) was used to calculate 1100 friction coefficients for heat extraction from air and carbon dioxide (ref. 6) for $0.3 < T_s/T_b < 1.0$ and $5 < x/D < 52$. Of the 1100 friction coefficients calculated, 94 percent deviated less than ± 15 percent and 88 percent deviated less than ± 10 percent from the measured values.

Figure 3 shows the product of the friction coefficient and the temperature ratio correction factor as a function of the modified surface Reynolds number. A total of 1523




Figure 3. - Correlation of local and average friction coefficients for modified surface Reynolds numbers of 3000 and greater. Density in friction coefficients evaluated at bulk temperature; viscosity in Reynolds number evaluated at surface temperature; 1523 data points in turbulent region. In ordinate D/x applies to local coefficients, D/L should be used for average coefficients.

friction coefficients for both the heating and cooling of gases were calculated using equation (9); 95 percent of the data are within ± 15 percent and 89 percent fall within ± 10 percent of the correlation line. The data in figure 3 indicate a lack of a transition region, except for the few points for air with a $T_s/T_b < 1.3$ that fall below the correlation line. Thus, it appears that the large variations in the fluid properties tend to make the flow turbulent at modified surface Reynolds numbers of 3000 or more.

CONCLUSIONS

Single-phase heat-transfer and friction coefficients for hydrogen, helium, nitrogen, air, and carbon dioxide with large variations in the physical properties have been studied. The coefficients were measured over a wide range of conditions outside the near-critical region for subsonic flow through smooth straight tubes. For the conditions stated, the following conclusions may be made:

1. For heat extraction from air and carbon dioxide with $0.25 < T_s/T_b < 1.0$ and $4 < x/D < 52$, there appears to be no discernable effect of either x/D or T_s/T_b on the heat-transfer coefficient and the equation

$$Nu_b = 0.023 Re_b^{0.8} Pr_b^{0.4}$$

where Nu_b is the bulk Nusselt number, Re_b is the bulk Reynolds number VD/ν_b , and Pr_b is the bulk Prandtl number, is recommended to predict heat-transfer coefficients. Using this equation, 80 percent of the calculated heat-transfer coefficients deviated less than ± 15 percent and 90 percent deviated less than ± 25 percent.

2. For heat addition to hydrogen, helium, nitrogen, air, and carbon dioxide with $1.0 < T_s/T_b < 23$ and $2 < x/D < 252$, there is a strong effect of both x/D and T_s/T_b . A total of 4900 heat-transfer coefficients were calculated with the relation

$$Nu_b = 0.023 Re_b^{0.8} Pr_b^{0.4} \left(\frac{T_s}{T_b} \right)^{-C_2}$$

where

$$C_2 = 0.57 - \frac{1.59}{\frac{x}{D}}$$

and Nu_b , Re_b , and Pr_b are the bulk Nusselt, Reynolds, and Prandtl numbers, respectively, T_s is the surface temperature, T_b is the fluid-bulk temperature, x is the axial distance from the entrance, and D is the inside diameter of the tube. Ninety percent of the calculated coefficients deviated less than ± 25 percent from the measured values.

3. Friction coefficients for heat addition to hydrogen, helium, nitrogen, air, and carbon dioxide with T_s/T_b to 7.35 and $5 < x/D < 200$ and heat extraction from air

and carbon dioxide with T_s/T_b as low as 0.30 and $5 < x/D < 57$ all show an effect of both x/D and T_s/T_b and have been accurately predicted by the relation

$$\frac{f}{2} = \left(0.0007 + \frac{0.0625}{\text{Re}_s^{0.32}} \right) \left(\frac{T_s}{T_b} \right)^{-C_2}$$

$$C_2 = 0.57 - \frac{1.59}{\frac{x}{D}}$$

where Re_s is the modified surface Reynolds number VD/ν_s , T_s is the surface temperature, T_b is the fluid-bulk temperature, x is the axial distance from the entrance, and D is the inside diameter of the tube. Of the 1100 friction coefficients calculated, 88 percent deviated less than ± 10 percent and 94 percent deviated less than ± 15 percent from the measured values.

Lewis Research Center,
National Aeronautics and Space Administration,
Cleveland, Ohio, December 30, 1970,
122-29.

REFERENCES

1. Taylor, Maynard F.: Correlation of Friction Coefficients for Laminar and Turbulent Flow with Ratios of Surface to Bulk Temperature from 0.35 to 7.35. NASA TR R-267, 1967.
2. Taylor, Maynard F.: Correlation of Local Heat-Transfer Coefficients for Single-Phase Turbulent Flow of Hydrogen in Tubes with Temperature Ratios to 23. NASA TN D-4332, 1968.
3. Dalle Donne, M.; and Bowditch, F. H.: High Temperature Heat Transfer. Nucl. Eng., vol. 8, no. 80, Jan. 1963, pp. 20-29.
4. Taylor, Maynard F.: Experimental Local Heat-Transfer Data for Precooled Hydrogen and Helium at Surface Temperatures up to 5300° R. NASA TN D-2595, 1964.


5. Petukhov, B. J.; Kirillov, V. V.; and Maidenik, V. N.: Heat-Transfer Experimental Research for Turbulent Gas Flow in Pipes at High Temperature Difference Between Wall and Bulk Fluid Temperature. Proceedings of the Third International Heat Transfer Conference. Vol. I. AIChE, 1966, pp. 285-292. (See also discussion by M. F. Taylor, Vol. 6, pp. 102-103.)
6. Wolf, Helmut: The Experimental and Analytical Determination of the Heat Transfer Characteristics of Air and Carbon Dioxide in the Thermal Entrance Region of a Smooth Tube with Large Temperature Differences Between the Gas and the Tube Wall. Ph.D. Thesis, Purdue University, 1958.
7. Zellnik, Herbert E.: Heat-Transfer from High Temperature Gases Inside Circular Tubes. Ph.D. Thesis, Univ. Michigan, 1956.
8. Taylor, Maynard F.: Experimental Local Heat-Transfer and Average Friction Data for Hydrogen and Helium Flowing in a Tube at Surface Temperatures up to 5600° R. NASA TN D-2280, 1964.
9. Perkins, H. C.; and Worsoe-Schmidt, P.: Turbulent Heat and Momentum Transfer for Gases in a Circular Tube at Wall-to-Bulk Temperature Ratios to Seven. Int. J. Heat Mass Transfer, vol. 8, 1965, pp. 1011-1031.
10. Davenport, Monty E.: The Effect of Transverse Temperature Gradients on the Heat Transfer and Friction for Laminar Flow of Gases. Tech. Rep. 247-3, Stanford Univ. (AEC Rep. TID-17792), 1962.
11. McEligot, D. M.: Effect of Large Temperature Gradients on Turbulent Flow of Gases in the Downstream Region of Tubes. Ph. D. Thesis, Stanford Univ., 1964.
12. Magee, P. M.: The Effect of Large Temperature Gradients on Turbulent Flow of Gases in the Thermal Entrance Region of Tubes. Tech. Rep. 247-4, Stanford Univ., 1964.

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

WASHINGTON, D. C. 20546

OFFICIAL BUSINESS

FIRST CLASS MAIL



POSTAGE AND FEES PAID
NATIONAL AERONAUTICS AND
SPACE ADMINISTRATION

POSTMASTER: If Undeliverable (Section 158
Postal Manual) Do Not Return

"The aeronautical and space activities of the United States shall be conducted so as to contribute . . . to the expansion of human knowledge of phenomena in the atmosphere and space. The Administration shall provide for the widest practicable and appropriate dissemination of information concerning its activities and the results thereof."

—NATIONAL AERONAUTICS AND SPACE ACT OF 1958

NASA SCIENTIFIC AND TECHNICAL PUBLICATIONS

TECHNICAL REPORTS: Scientific and technical information considered important, complete, and a lasting contribution to existing knowledge.

TECHNICAL NOTES: Information less broad in scope but nevertheless of importance as a contribution to existing knowledge.

TECHNICAL MEMORANDUMS: Information receiving limited distribution because of preliminary data, security classification, or other reasons.

CONTRACTOR REPORTS: Scientific and technical information generated under a NASA contract or grant and considered an important contribution to existing knowledge.

TECHNICAL TRANSLATIONS: Information published in a foreign language considered to merit NASA distribution in English.

SPECIAL PUBLICATIONS: Information derived from or of value to NASA activities. Publications include conference proceedings, monographs, data compilations, handbooks, sourcebooks, and special bibliographies.

TECHNOLOGY UTILIZATION PUBLICATIONS: Information on technology used by NASA that may be of particular interest in commercial and other non-aerospace applications. Publications include Tech Briefs, Technology Utilization Reports and Notes, and Technology Surveys.

Details on the availability of these publications may be obtained from:

SCIENTIFIC AND TECHNICAL INFORMATION DIVISION
NATIONAL AERONAUTICS AND SPACE ADMINISTRATION
Washington, D.C. 20546